

## Digital thermostatic baths "DIGIBATH"



**BAD-4**

### Features:

Temperature regulation by microprocessor with digital read out and P.I.D. action. PT100 probe. Programmable delayed start (0-99,5 hours). Programmable incubation time (0-99,5 hours).

Safety under Regulation

EN 61010-1

Safety thermostat with manual rearms according to DIN 12877 Class 2

Inner tank made in AISI 304 stainless steel.

External case made in AISI 304 Stainless steel heating elements inside the tank.

Incorporated drainage

Series	Regulation	Temperature range	Temperature stability	Homogeneity	Resolution
<b>BAD</b>	Digital	Room temp. +5° - 99,9° C	± 0,15° C	± 1° C	0,1° C
<b>BOD</b>	Digital	Room temp. +5° - 200° C	± 0,4° C	± 2° C	1° C

Reference	Capacity l.	Int. H x W x D in mm	Ext. H x W x D in mm	Power W	Weight kg.
<b>BAD-2</b>	5	120 x 295 x 140	210 x 345 x 190	600	5
<b>BAD-4</b>	12	120 x 295 x 320	210 x 345 x 470	1200	7,5
<b>BAD-6</b>	20	120 x 490 x 290	210 x 345 x 645	1600	10
<b>BAD-12</b>	40	120 x 620 x 500	210 x 665 x 645	2400	15
<b>BOD-2</b>	5	120 x 295 x 140	210 x 345 x 190	1000	5
<b>BOD-4</b>	12	120 x 295 x 320	210 x 345 x 470	1500	7,5
<b>BOD-6</b>	20	120 x 490 x 290	210 x 345 x 645	2000	10
<b>BOD-12</b>	40	120 x 620 x 500	210 x 665 x 645	3200	15

## Digital thermostatic baths "DIGIBATH" Accessories

Concentric rings lid

**TB-6**



Roof type lid

**TT-6**




Heater protecting tray

**TI-6**



Support frames

**MB001, MB002, MB003**



Bath series	Capacity l.	Heater protecting tray	Concentric rings lid	Roof type lid	Support frame
BAD, BOD	5	TI-2	TB-2	TT-2	MB001
BAD, BOD	12	TI-4	TB-4	TT-4	MB002
BAD, BOD	20	TI-6	TB-6	TT-6	MB003
BAD, BOD	40	TI-12	TB-12	TT-12	MB003 (2 u)

### Rack with handles



Reference

Description

GRB-5613	56 tubes (14 x 4) Ø 13 mm
GRB-4816	48 tubes (12 x 4) Ø 16 mm
GRB-3020	30 tubes (10 x 3) Ø 20 mm

Thermostatic baths