



MTS 2/4 digital microtiter shaker

Newly developed special shaker for shaking two or four microtiter plates.

- Electronic speed control
- Digital timer
- Alarm to indicate set time has expired
- Incl. attachment (without microtiter plate)

Accessories: H 11 Mains cable UK plug, H 11 Mains cable CH plug, H 11 Mains cable USA plug, H 11 Mains cable Euro plug

Technical Data

Type of movement	orbital
Shaker diameter [mm]	3
Permissible shaking weight (incl. attachment) [kg]	2/4 MT-Platten
Motor rating input [W]	35
Motor rating output [W]	13.2
Permissible ON time [%]	100
Speed min (adjustable) [rpm]	50
Speed range [rpm]	0 - 1100
Speed display	scale
Timer	yes
Timer display	7 segment LED
Time setting range [min]	1 - 99
Operating mode	timer and continuous operation
Shaking table lock	no
Working with microtiter plates	yes
Number of microtiter plates	2 or 4
Dimensions (W x H x D) [mm]	185 x 105 x 320
Weight [kg]	2.7
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 21
RS 232 interface	no
Analog output	no
Voltage [V]	220 - 240 / 100 - 120
Frequency [Hz]	50/60
Power input [W]	45

Ident. No. 0003208000