

Bank of thermostatic baths



BBA-6

Features:

Inner tank and external case made of AISI-304 stainless steel.
 Hydraulic thermostat with graduated scale in °C, and pilot light.
 Safety thermostat with manual rearm. It switches off the instrument in the case of over-temperature or lack of liquid in the tank, in accordance with DIN 12.877 Class 2 regulation.
 Cover resistance tray included.

Reference	Places	Temperature	Ext. Ø x H in mm	Ext. Ø x H in mm	Power W	Weight kg
BBA-2	2	Room temp. +5° -110° C	120 x 150 x 130	220 x 340 x 240	800	6
BBA-4	4	Room temp. +5° -110° C	120 x 150 x 130	220 x 670 x 240	1600	10,5
BBA-6	6	Room temp. +5° -110° C	120 x 150 x 130	220 x 1000 x 240	2400	16
BBO-2	2	Room temp. +5° -200° C	120 x 150 x 130	220 x 340 x 240	1400	6
BBO-4	4	Room temp. +5° -200° C	120 x 150 x 130	220 x 670 x 240	2800	10,5
BBO-6	6	Room temp. +5° -200° C	120 x 150 x 130	220 x 1000 x 240	4200	16

Accessories

Boshead up to 16 mm.
 Three prong clamp.
 Heater protecting tray.

Reference: 2202
Reference: 2802
Reference: TI-1

