

# AUTOCLAVES

***PBI Autoclaves  
in more than  
100 countries***



# BETA EASY-LOCK

## AUTOCLAVES

### PBI AUTOCLAVES IN MORE THAN 100 COUNTRIES

#### RELIABILITY

High resistance to perforating corrosion.  
Outside structure and inside pressure vessel  
manufactured from mirror finished AISI 304  
stainless steel for easy cleaning and  
sanitizing.

#### OVER NIGHT CYCLE

Is it possible to  
delay the cycle  
start.

#### EASY CLOSURE

"Easy-Lock" system  
to be used with a  
single hand.

#### SAFETY

"ABS" insulating  
cover with vertical  
position lock.

#### TRACEABILITY

Printer  
(on request).

#### FRIENDLY USE

User friendly  
instruction panel  
according to GLP.

#### FLEXIBILITY

Two models with 25 and 50 litres volume.  
Vertical loading to maximize usable vessel space.  
Up to seven personal passwords protected programs.

#### CERTIFICATION

Conforms to PED Directive.  
CE marked.  
Special fitting for certified  
thermo-probe to perform  
validation.

#### WORKING TEMPERATURE/PRESSURE

Up to 134 °C (2.1 atm).

#### F<sub>0</sub> FUNCTION

Ideal to protect the  
thermosensitive products.  
Only for 50 litres models.



- **R**educed energy
- **R**e-cyclable material
- **R**e-usable components



# BETA EASY-LOCK

AUTOCLAVES



## 4 GOOD REASONS TO CHOOSE THE "BETA" AUTOCLAVE MODEL

### GOOD LABORATORY PRACTICE

- Special fitting for insertion of certified thermo-probe to perform validation
- I.Q., O.Q., P.Q documentation available on request
- "Data Print" printer (optional)
  1. Date, lot number, cycle progressive number, temperature
  2. Interval time programming during sterilization cycle

### SAFETY AND ERGONOMY

- "ABS" insulating cover conforms to safety regulations
- "Easy-Lock" closure to be operated with just one hand
- Safety lid lock to avoid accidental closure
- Safety thermostat for low level water control on Beta 25
- Water sensor on Beta 50

### AUTOMATIC THERMOREGULATION


- Up to 7 automatic and personal sterilization cycles
- Friendly user program panel
- End-cycle acoustic signal
- Programmed temperature, real temperature, and sterilization time visual presentation
- Cycle start can be delayed

### RELIABILITY

- Outside structure and inside pressure vessel manufactured from mirror-finished AISI 304 stainless steel for easy cleaning and sanitizing
- Robust AISI 304 Stainless steel basket
- Reinforced heating element



*one hand "Easy Lock" closure*



*safety lid lock to avoid casual closure*

# BETA EASY-LOCK

AUTOCLAVES



MODEL	BETA 25	BETA 50
Volume	25 litres	50 litres
Vessel dimensions	Ø 250x450 h mm	Ø 320x600 h mm
External dimensions	550x540x1005 h mm	550x570x1005 h mm
Programs	5 personal programs	7 personal programs
Thermo-probe	Fixed PT100	Flexible PT100
Max pressure	2.1 atm (134 °C)	2.1 atm (134 °C)
Power supply	220 V (50 Hz) - 1700 W	380 V triphase (50 Hz) - 3700 W
	Other electrical configurations available on request	
Weight	45 kg	60 kg
Loading solutions: number and types of baskets	A	1 Macrobox (cod. 5422)
	B	2 Minibox (cod. 5421)
	C	-

Loading examples	500 ml bottles	1000 ml bottles	2000 ml bottles	2000 ml flasks
BETA 25* basket diameter d24 cm	 4	 3	 1	 1
BETA 50* basket diameter d31 cm	 8	 5	 3	 3

\* check the height of the load to stack the baskets



## WHAT TO ORDER

### Autoclave Beta 25 Easy-Lock

**91225** autoclave "Beta 25 Easy-Lock" - vol. 25 litres - 10 years warranty against corrosion perforation

#### Accessories

**5422** "Macrobox" basket - ext. dim. Ø 24x42 cm - stainless steel AISI 304 - MAX one basket loading

**5421** "Minibox" basket - ext. dim. Ø 24x21 cm - stainless steel AISI 304 - MAX two baskets loading

### Autoclave Beta 50 Easy-Lock

**91382** autoclave "Beta 50 Easy-Lock" - vol. 50 litres - 10 years warranty against corrosion perforation

#### Accessories

**48850** "Betabox 50" basket - ext. dim. Ø 31x28,5 cm - stainless steel AISI 304 - MAX two baskets loading

**89213** "Betabox" basket - ext. dim. Ø 31x38 cm - stainless steel AISI 304 - MAX one basket loading

**89214** "Betabox-Mini" basket - ext. dim. Ø 31x19 cm - stainless steel AISI 304 - MAX two baskets loading

#### Accessories for all models

**78383** "Data-Print" printer

#### Documentation

*IQ, OQ, PQ documentation available on request*