

TW20 Water Bath

4 different models from 2 to 26 liter

The TW series offers high-quality water baths MICROPROCESSOR technology and a temperature stability of ± 0.2 °C. The working temperature range offers many application possibilities, e.g. routine laboratory applications, temperature control of samples, incubations, dental applications, material testing, corrosion tests, tempering of cultures as well as temperature testing of food and luxury articles. The units are provided with overall splash-water protection and have a keypad for temperature settings and with temperature indication (LED) for easy operation. Dry-running protection as well as optical and acoustical warnings, and switch-off functions, offer maximum protection for sensitive goods which require to be temperature controlled. There are a wide range of accessories including test tube racks and lift-up Makrolon covers available.



Your advantages

- MICROPROCESSOR technology with PID temperature control
- Bright MULTI-DISPLAY (LED)
- Seamless, splash-proof keypad
- Splash-proof mains switch
- Early warning system with high and low temperature limits
- Drain screw for conveniently emptying the bath
- Dry-running protection / safety temperature fixed at 130 °C
- Wide range of accessories including lift-up Makrolon bath cover available

Technical Data

Order No.	9550120
Model series	TW Series - water baths
Category	Water Baths & Shaking Water Baths
Working temperature range (°C)	20 99.9
Temperature stability (°C)	±0.2
Setting / display resolution	0.1 °C
Temperature Display	LED
Heating capacity (kW)	2
Bath opening / bath depth (W x L / D cm)	50 x 30 / 18
Filling volume liters	826
Ambient temperature	540 °C

JULABO GmbH | Eisenbahnstrasse 45 | 77960 Seelbach/Germany
Tel: +49 (0) 7823 / 510 | Fax: +49 (0) 7823 / 2491 | info@julabo.de | www.julabo.de

Product data sheet



Dimensions W x L x H (cm)	56 x 35 x 32
Weight (kg)	20
Classification according to DIN12876-1	Classification I (NFL)according to DIN 12876-1
Bath cover	optional

Available voltage versions

230 V / 50-60 Hz 115 V / 60 Hz

Characteristics



Easy to read

Large LED temperature display for actual value and setpoint (resolution $0.1~^{\circ}\text{C})$



Time saving

Comfortable and simple operation for setpoint adjustment

Other characteristics

Lift-up Makrolon bath cover available (order-nr. 8970289).

Technical changes without prior notification. Images may deviate from the original.