



F12-MA



F25-MA



FP35-MA

TopTech Series


for working temperatures from -50 °C to +200 °C

Refrigerated/heating circulators of the TopTech series are designed for more demanding applications. They feature increased functionality and additional warning and safety functions.


Models with MA circulators

- PID2 temperature control, stability ± 0.02 °C
- ATC 3-point calibration
- RS232 interface
- Early warning system for low liquid level and high/low temperature
- Pump capacity electronically adjustable
- Protection class III according to DIN 12876-1


Heat-up time
Bath fluid: Thermal



Cool-down time
Bath fluid: Thermal



Heat-up/cool-down time
Bath fluid: Thermal



JULABO Order No.	JULABO Model	Working temp. range °C	Temp. stab. °C	Heat. cap. kW	Cooling capacity kW (Bath fluid: Ethanol)					Pump capacity		Bath opening/ Bath depth W x L/D cm	Fill. vol. liters	Dimensions W x L x H cm
					+20	0	-20	-30	-40 °C	Flow rate/Pressure l/min. bar				
9 153 612	F12-MA	-20 ... +200	± 0.02	2	0.16	0.1	0.02	--	--	11-16	0.23-0.45	13 x 15 / 13	4.5	20 x 36 x 56
9 153 625	F25-MA	-28 ... +200	± 0.02	2	0.26	0.2	0.06	--	--	11-16	0.23-0.45	12 x 14 / 14	4.5	23 x 42 x 61
9 153 625N	FN25-MA	-28 ... +200	± 0.02	2	0.26	0.2	0.06	--	--	11-16	0.23-0.45	12 x 14 / 14	4.5	23 x 50 x 61
9 153 632	F32-MA	-35 ... +200	± 0.02	2	0.45	0.39	0.15	0.06	--	11-16	0.23-0.45	18 x 12 / 15	8	31 x 42 x 64
9 153 632N	FN32-MA	-35 ... +200	± 0.02	2	0.45	0.39	0.15	0.06	--	11-16	0.23-0.45	18 x 12 / 15	8	31 x 50 x 64
9 153 633	F33-MA	-30 ... +200	± 0.02	2	0.5	0.32	0.12	0.03	--	11-16	0.23-0.45	23 x 14 / 20	16	36 x 46 x 69
9 153 634	F34-MA	-30 ... +150	± 0.02	2	0.45	0.32	0.14	0.03	--	11-16	0.23-0.45	24 x 30 / 15	20	38 x 58 x 62
9 153 618	FP35-MA	-35 ... +150	± 0.02	2	0.45	0.39	0.15	0.05	--	11-16	0.23-0.45	18 x 12 / --	2.5	31 x 42 x 64
9 153 640	FP40-MA	-40 ... +200	± 0.02	2	0.68	0.5	0.32	0.17	0.04	11-16	0.23-0.45	23 x 14 / 20	16	37 x 46 x 69
9 153 650	FP50-MA	-50 ... +200	± 0.02	2	0.9	0.8	0.5	0.32	0.16	11-16	0.23-0.45	18 x 12 / 15	8	42 x 49 x 70

water-cooled model

9 153 651	FPW50-MA	-50 ... +200	± 0.02	2	0.9	0.8	0.5	0.32	0.16	11-16	0.23-0.45	18 x 12 / 15	8	42 x 49 x 70
-----------	----------	--------------	------------	---	-----	-----	-----	------	------	-------	-----------	--------------	---	--------------

Included with each unit: 2 each barbed fittings for tubing 8 and 10 mm inner dia. (pump connections M10x1 female)



F26-ME

FN32-ME

FP50-ME

TopTech Series

for working temperatures from -50 °C to +200 °C

Models with ME circulators allow for a wide range of applications. The units have a connection for an external Pt100 sensor for direct measuring and control in an external application. The VFD Comfort display features easy operation and shows all temperature values on one display.

Additional advantages of models with ME circulators

- PID3 temperature control, stability ± 0.01 °C
- VFD Comfort Display with simultaneous indication of setpoint and internal and external actual value (resolution 0.01 °C)
- Integrated programmer (1 x 10 steps) with real-time clock
- Illuminated display for adjustable pump capacity


Note: FP models feature an energy-saving proportional cooling control.



More information on circulators with natural refrigerants on page 22


Cool-down time

Bath fluid: Ethanol



Pump capacity

Bath fluid: water



JULABO Order No.	JULABO Model	Working temp. range °C	Temp. stab. °C	Heat. cap. kW	Cooling capacity kW (Bath fluid: Ethanol)					Pump capacity Flow rate/Pressure l/min. bar		Bath opening/ Bath depth W x L/D cm	Fill. vol. liters	Dimensions W x L x H cm
					+20	0	-20	-30	-40 °C					
9 162 625	F25-ME	-28 ... +200	± 0.01	2	0.26	0.2	0.06	--	--	11-16	0.23-0.45	12 x 14 / 14	4.5	23 x 42 x 61
9 162 625N	FN25-ME	-28 ... +200	± 0.01	2	0.26	0.2	0.06	--	--	11-16	0.23-0.45	12 x 14 / 14	4.5	23 x 50 x 61
9 162 626	F26-ME	-28 ... +200	± 0.01	2	0.26	0.2	0.06	--	--	11-16	0.23-0.45	12 x 14 / 14	4.5	42 x 42 x 42
9 162 632	F32-ME	-35 ... +200	± 0.01	2	0.45	0.39	0.15	0.06	--	11-16	0.23-0.45	18 x 12 / 15	8	31 x 42 x 64
9 162 632N	FN32-ME	-35 ... +200	± 0.01	2	0.45	0.39	0.15	0.06	--	11-16	0.23-0.45	18 x 12 / 15	8	31 x 50 x 64
9 162 633	F33-ME	-30 ... +200	± 0.01	2	0.5	0.32	0.12	0.03	--	11-16	0.23-0.45	23 x 14 / 20	16	36 x 46 x 69
9 162 634	F34-ME	-30 ... +150	± 0.01	2	0.45	0.32	0.14	0.03	--	11-16	0.23-0.45	24 x 30 / 15	20	38 x 58 x 62
9 162 640	FP40-ME	-40 ... +200	± 0.01	2	0.68	0.5	0.32	0.17	0.04	11-16	0.23-0.45	23 x 14 / 20	16	37 x 46 x 69
9 162 650	FP50-ME	-50 ... +200	± 0.01	2	0.9	0.8	0.5	0.32	0.16	11-16	0.23-0.45	18 x 12 / 15	8	42 x 49 x 70
water-cooled model														
9 162 651	FPW50-ME	-50 ... +200	± 0.01	2	0.9	0.8	0.5	0.32	0.16	11-16	0.23-0.45	18 x 12 / 15	8	42 x 49 x 70

Included with each unit: 2 each barbed fittings for tubing 8 and 10 mm inner dia. (pump connections M10x1 female)